

FORM PTO-1300

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY DOCKET NUMBER
WATE-0011TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

U.S. APPLICATION NO. of (known) (see 37 C.F.R. 1.5)

097/980562

INTERNATIONAL APPLICATION NO.
PCT/AU00/00420INTERNATIONAL FILING DATE
05 May 2000PRIORITY DATE CLAIMED
05 May 1999TITLE OF INVENTION **INDUSTRIAL PRESS SAFETY SYSTEM**APPLICANT(S) FOR DO/EO/US **Robert APPLEYARD**

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☒ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) 35 U.S.C. 371(c)(4).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
14. ☐ A SECOND or SUBSEQUENT preliminary amendment.
15. ☐ A substitute specification.
16. ☒ A change of power of attorney and/or address letter.
17. ☒ Other items or information:
 - A copy of the **Published PCT Application** by WIPO under No. **WO 00/67932**, including the search report.
 - A copy of the **International Preliminary Examination Report**.

EXPRESS MAIL Mailing Label No. **EL 922205439 US**Date of Deposit: **01 November 2001**

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

MAILER

John Hill

SIGNATURE

EL 922205439 US

U.S. APPLICATION NO. (if known) 09/980562 PCT/USAU/00420		INTERNATIONAL APPLICATION NO. PCT/USAU/00420		ATTORNEY DOCKET NUMBER WATE-0011	
17. The following fees are submitted: Basic National Fee (37 CFR 1.492(a)(1) - (5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO..... \$1,040.00 International preliminary examination fee (37 CFR 1.482 not paid to USPTO but International Search Report has been prepared by the EPO or JPO..... \$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO..... \$740.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4)..... \$710.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)..... \$100.00					
ENTER APPROPRIATE BASIC FEE AMOUNT —				\$890.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than _ 20 _ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
Claims	Number Filed	Number Extra	Rate		
Total claims	-20 =		X \$18.00	\$	
Independent Claims	- 3 =		x \$84.00	\$	
Multiple dependent claims(s) (if applicable)			+ \$280.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$890.00	
___ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$	
SUBTOTAL =				\$890.00	
Processing fee of \$130.00 for furnishing the English translation later than _ 20 _ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				+	\$
TOTAL NATIONAL FEE =				\$890.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				+	
TOTAL FEES ENCLOSED =				\$890.00	
				Amount to be:	
				refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$ 890.00 to cover the above fee is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. 23-3050 in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input type="checkbox"/> The Commissioner if hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 23-3050. A duplicate copy of this sheet is enclosed.					
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO: David A. Cherry Woodcock Washburn LLP One Liberty Place - 46th Floor Philadelphia, PA 19103 (215) 568-3100					
				SIGNATURE	
				NAME	
				David A. Cherry	
				35,099	
REGISTRATION NUMBER					

09980562 .061102
Rec'd PCT/PTO 04 FEB 2002

09/98 0562

DOCKET NO.: WATE-0011

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Robert Appleyard

Serial No.: 09/980,562

Group Art Unit: Not yet assigned

Intl. Application No.: PCT/AU00/00420

Examiner: Not yet assigned

International Filing Date: 05 May 2000

For: INDUSTRIAL PRESS SAFETY

Assistant Commissioner
for Patents
Washington, D.C. 20231

Dear Sir:

PRELIMINARY AMENDMENT

Please make the amendments to the above-identified application as follows:

In the claims:

Amend claims 1, 5, 6, 7, 8, 11-13, 15-17, 19 and 20, claim 21 has been added as follows:

1. (Amended) A safety system for an industrial press having a moveable section, the safety system comprising:

a laser emitting means for emitting a continuous planar laser beam having a generally constant lateral width;

a light receiving means for receiving the laser beam and for detecting when an object intersects the laser beam; and

DOCKET NO.: WATE-0011**PATENT**

a control means for stopping or preventing a movement of the moveable section of the press when the receiving means detects that the laser beam has intersected an object.

5. (Amended) A safety system according to claim 2, wherein the laser emitting means and the light receiving means is mountable on or immediately adjacent the blade, and is movable with the blade when it is the moveable section of the press.

6. (Amended) A safety system according to claim 1, further comprising a plurality of laser emitting means and associated said light receiving means for emitting a plurality of said planar laser beams.

7. (Amended) A safety system according to claim 1, wherein the laser emitting means includes a laser emitter for emitting a laser beam, and a lens assembly for varying the configuration of the laser beam into a said planar laser beam of generally planar shape and having a generally constant lateral width.

8. (Amended) A safety system according to claim 7, wherein the lens assembly includes a cylindrical prism for initially expanding the laser beam into a laser beam having a planar fan shaped configuration, and a converging lens for refocusing the fan shaped laser beam to a planar laser beam having a generally constant lateral width.

11. (Amended) A safety system according to claim 9, wherein the correcting means includes a lens series having at least one convex and at least one concave lens.

12. (Amended) A safety system according to claim 7, wherein the light receiving means includes a receiver body, and a plurality of light receivers aligned along a common axis as a light receiver array and located at one end of the receiver body, wherein each light receiver is

DOCKET NO.: WATE-0011**PATENT**

located at one end of a respective light receiving passage provided through the receiver body.

13. (Amended) A safety system according to claim 7, wherein the light receiving means includes a receiver body, a plurality of light receivers aligned along a common axis as a light receiver array and located at one end of the receiver body, and a lens provided at the opposing end of the receiver body for focusing the planar laser beam onto the light receivers.

15. (Amended) A safety system according to claim 14, wherein the receiver body is an enclosure separated into separate parallel passages by dividing walls.

16. (Amended) A safety system according to claim 12, wherein the width of the planar laser beam is wider than the length of the light receiver array.

17. (Amended) A safety system according to claim 12, further including an electronic control unit for receiving control signals from the light receivers and for controlling the operation of the press, wherein the press is stopped when the receipt of the light of the laser beam to at least one of the light receivers is blocked due to a breaking of the planar beam.

19. (Amended) A safety system according to claim 1, wherein both the laser emitting means and the light receiving means are respectively mounted on supports on opposing sides of the moveable section of the press, wherein at least one of the supports is adjustable to allow the alignment and position of at least one of the laser emitting means or the light receiving means to be adjusted.

20. (Amended) A safety system according to claim 19, wherein only the laser emitting means is adjustable, the light receiving means remaining in a fixed position.

DOCKET NO.: WATE-0011

PATENT

21. (New) A safety system for an industrial press having a moveable section, the safety system comprising:

a laser that emits a continuous planar laser beam having a generally constant lateral width;

a light receiver, aligned with the laser, that receives the laser beam and detects when an object intersects the laser beam; and


a control, in electronic communication with the light receiver, that is capable of stopping or preventing a movement of the moveable section of the press when the light receiver detects that the laser beam has intersected an object.

REMARKS

The amendments submitted herein put the claims in accordance with U.S. practice, eliminate multiple dependencies, and correct minor typographical errors. None of the amendments submitted herein narrow the scope of any limitation.

Applicant requests entry of this amendment prior to examination, and favorable consideration.

Respectfully submitted,



Harold H. Fullmer

Registration No. 42,560

Date: Feb 4, 2002

WOODCOCK WASHBURN KURTZ
MACKIEWICZ & NORRIS LLP
One Liberty Place - 46th Floor
Philadelphia, PA 19103
(215) 568-3100

DOCKET NO.: WATE-0011

PATENT

VERSION SHOWING MARKINGS FOR CHANGES MADE

In the claims:

Claims 1, 5, 6, 7, 8, 11-13, 15-17, 19 and 20 have been amended and claim 21 has been added as follows:

1. (Amended) A safety system for an industrial press having a moveable section, the safety [means including] system comprising:

a laser emitting means for emitting a continuous planar laser beam having a generally constant lateral width;

a light receiving means for receiving the laser beam and for detecting when an object intersects the laser beam; and

a control means for stopping or preventing a movement of the moveable section of the press when the receiving means detects that the laser beam has intersected an object.

5. (Amended) A safety system according to any one of [claims 2 to 4] claim 2, wherein the laser emitting means and the light receiving means is mountable on or immediately adjacent the blade, and is movable with the blade when it is the moveable section of the press.

6. (Amended) A safety system according to [any one of the preceding claims] claim 1, [including] further comprising a plurality of laser emitting means and associated said light receiving means for emitting a plurality of said planar laser beams.

7. (Amended) A safety system according to [any one of the preceding claims] claim 1, wherein the laser emitting means includes a laser emitter for emitting a laser beam, and a lens assembly for varying the configuration of the laser beam into a said planar laser beam of generally planar shape and having a generally constant lateral width.

DOCKET NO.: WATE-0011

PATENT

8. (Amended) A safety system according to claim 7, wherein the lens assembly includes a cylindrical prism for initially expanding the laser beam into a laser beam having a planar fan shaped configuration, and a converging lens for [refocussing] refocusing the fan shaped laser beam to a planar laser beam having a generally constant lateral width.

11. (Amended) A safety system according to claim 9 [or 10], wherein the correcting means includes a lens series having at least one convex and at least one concave lens.

12. (Amended) A safety system according to [any one of the preceding claims] claim 7, wherein the light receiving means includes a receiver body, and a plurality of light receivers aligned along a common axis as a light receiver array and located at one end of the receiver body, wherein each light receiver is located at one end of a respective light receiving passage provided through the receiver body.

13. (Amended) A safety system according to [any one of the preceding claims] claim 7, wherein the light receiving means includes a receiver body, a plurality of light receivers aligned along a common axis as a light receiver array and located at one end of the receiver body, and a lens provided at the opposing end of the receiver body for focusing the planar laser beam onto the light receivers.

15. (Amended) A safety system according to claim [13 or] 14, wherein the receiver body is an enclosure separated into separate parallel passages by dividing walls.

16. (Amended) A safety system according to [any one of] claim[s] 12 [to 15], wherein the width of the planar laser beam is wider than the length of the light receiver array.

17. (Amended) A safety system according to [any one of claims 12 to 16] claim

DOCKET NO.: WATE-0011

PATENT

12, further including an electronic control unit for receiving control signals from the light receivers and for controlling the operation of the press, wherein the press is stopped when the receipt of the light of the laser beam to at least one of the light receivers is blocked due to a breaking of the planar beam.

19. (Amended) A safety system according to [any one of the preceding claims] claim 1, wherein both the laser emitting means and the light receiving means are respectively mounted on supports on opposing sides of the moveable section of the press, wherein at least one of the supports is adjustable to allow the alignment and position of at least one of the laser emitting means or the light receiving means to be adjusted.

20. (Amended) A safety system according to claim 19, wherein only the laser emitting means is adjustable, the light receiving [mans] means remaining in a fixed position.

21. (New) A safety system for an industrial press having a moveable section, the safety system comprising:

a laser that emits a continuous planar laser beam having a generally constant lateral width;

a light receiver, aligned with the laser, that receives the laser beam and detects when an object intersects the laser beam; and

a control, in electronic communication with the light receiver, that is capable of stopping or preventing a movement of the moveable section of the press when the light receiver detects that the laser beam has intersected an object.

INDUSTRIAL PRESS SAFETY SYSTEM

The present invention is generally directed to safety systems used in industrial applications, and in particular to safety systems for use on industrial presses such as a press brake or guillotine.

5 The dangers associated with the operation of industrial presses has necessitated the development of various safety arrangements to protect workers using such presses. Safety light curtain systems are commonly used to provide a plurality of parallel infrared (IR) light beams as a "barrier" for the press. The breaking of any of the IR light beams by the operator of the press
10 results in the stopping of the operation of the press. These safety light curtains must however be located a significant distance in front of the press to operate with any effectiveness. This is because of the degree of dispersion of the IR light beams over the extended distances limits the accuracy and speed of operation of such light curtains.

15 In British Patent No. 1307078, there is described a light curtain guard for a press brake of the kind having an upward stroking ram, commonly known as an upstroking press brake. The light curtain guard is also formed by a series of parallel light beams, the main difference being that the light curtain guard is supported on and moveable with the upward stroking ram. It should
20 be noted that both upstroking press brakes and downstroking press brakes having a downward stroking ram are well known in the market.

Cynum Industrie S.A. have since around 1981 been marketing a press brake having a safety apparatus including a laser emitter and receiver mounted on opposing sides of the bottom anvil of the press brake and
25 emitting single laser beam close to the surface of the anvil. In an upstroking machine, the laser emitter and receiver move together with the anvil.

In Australian Patent No. 667057, there is described a safety apparatus for use on a downstroking press brake having a moving upper blade and stationary anvil. The safety apparatus differs from the Cynum press brake in
30 being mounted on the upper blade rather than on the anvil, the safety apparatus otherwise operating in the same manner by emitting at least one beam of light in close relation to the leading edge of the upper blade. The light beam can be either an IR or a laser beam.

Fiessler Elektronik are marketing a press brake safety apparatus similar to the apparatus described in the abovenoted Australian Patent, but includes additional parallel laser beams for providing a larger safety zone adjacent the upper blade of the press brake.

5 In all of the above-described systems the breaking of the one or more light beams causes the press brake to stop or prevents the press brake from operating. Furthermore, the safety apparatus in all of the above press brakes are mounted on and movable with the moving part of the press brake, whether it is the upper blade or the bottom anvil.

10 The above noted systems however have certain disadvantages. Firstly because all of the above arrangements rely on one or a series of parallel IR or laser beams to provide a barrier, there is always the possibility of the safety light curtain being inadvertently bypassed by an object passing the light beam or passing between adjacent parallel light beams and not breaking any of the
15 light beams. The single light beam or safety light curtain is therefore ineffectual under these circumstances.

Also, in the case of arrangements using laser beams, vibrations can seriously distort the path of the laser beam causing disruptions and inaccuracies in the operation of such arrangements. Although the use of
20 software "filtering" or compensation can be used to minimise the effect of vibrations as for example shown in International Application No. PCT/AU97/00005, this results in an increase in the delay between the breaking of the light beam and the subsequent actuation of the safety system to stop the press. Such delays should preferably be minimised as far as
25 possible, and preferably eliminated.

It is therefore an object of the present invention to provide a safety system for an industrial press that overcomes at least one of the disadvantages associated with the prior art.

30 With this in mind, the present invention provides a safety system for an industrial press having a moveable section, the safety means including: a laser emitting means for emitting a continuous planar laser beam having a generally constant lateral width;

WO 00/67932

PCT/AU00/00420

3

a light receiving means for receiving the laser beam and for detecting when an object intersects the laser beam; and

a control means for stopping or preventing movement of the moveable section of the press when the receiving means detects that the laser beam has intersected an object.

The use of a continuous planar laser beam having a generally constant lateral width means that the laser beam can cover a relatively wide area when compared with a conventional laser beam while at the same time ensuring that there are no "spaces" through which an object can pass without detection.

The industrial press can for example be a press brake having a blade and an anvil moveable relative to each other. The laser beam may be emitted immediately adjacent the leading edge of the blade. According to one preferred embodiment of the present invention, the plane of the laser beam may be horizontal and located between the blade and anvil of the press brake. Furthermore, the laser emitting means and the light receiving means may be mountable on the blade, and may move with the blade if that part is the moveable section of the press brake. This ensures that the introduction of an object close enough to the blade to intersect the laser beam will stop or prevent the operation of the press. Alternative orientations of the laser beam are however also envisaged. For example, the laser beam can be emitted in front of the blade with the plane of the laser beam being generally vertical. Alternatively, the safety system may emit a plurality of planar laser beams. For example, laser beams can be emitted both in front of and under the cutting blade. This provides an "L"-shaped configuration of planar laser beams.

The laser emitting means may include a laser emitter, for example a laser diode for emitting a laser beam, and a lens assembly for varying the configuration of the laser beam emitted from the laser diode. Laser beams emitted by such laser emitters are typically circular in cross section. The lens assembly converts this laser beam into a laser beam of generally planar shape and having a generally constant lateral width. It should be noted that some dispersion of the laser beam may occur the further away a point on the laser beam is from the laser emitter. This dispersion is however relatively

WO 00/67932

PCT/AU00/00420

4

insignificant within the range of distances that the laser beam must be emitted over, typically between 2 to 12 metres.

The lens assembly may include a cylindrical prism for initially expanding the laser beam into a laser beam having a planar fan shaped configuration. The lens assembly may also include a converging lens for refocussing the fan shaped laser beam to a planar laser beam having a generally constant lateral width. The original laser beam emitted from the laser emitter has virtually parallel "lines of light". The light intensity when measured across the lateral width of the planar laser beam can however vary.

This is due to the refractive effect of the lens on the laser beam which can cause a deflection in the lines of light within the laser beam resulting in an overlapping of the lines of light therein. The "shadow" produced by an object intersecting the laser beam may therefore not be detected by the receiving means as the lines of light passing the object can overlap thereby obscuring any shadow produced by the object. A correcting lens may therefore need be provided after the converging lens to straighten the lines of light of the laser beam refocussed through the converging lens. This correcting lens may for example be in the form of a lenticular lens having a plurality of lens sections which respectively straighten the portion of the laser beam passing therethrough. Alternatively, a series of separate parallel lenses may be placed side to side in front of the converging lenses, each lens correcting a portion of the laser beam. This will ensure that the lines of light of the laser beam are generally parallel, and that an object intersecting the corrected laser beam will cast a clear shadow on the receiving means. According to another preferred arrangement, the lines of light of the laser beam may be straightened by a series of correcting lenses located one after each other. For example, the lens series may include a combination of a convex and concave lens located in series. This lens series may be used in place of or together with the lenticular lens. Additional lenses may be provided depending on the required accuracy of the correction of the planar laser beam.

The light receiving means may include a plurality of electronic light receivers aligned on along a common axis as a light receiver array. The light receiver array may be located at one end of a receiver body. Each light

WO 00/67932

PCT/AU00/00420

5

receiver may be located at the end of a light receiving passage provided through the receiver body to prevent other light, eg. reflected light, from effecting the reading obtained from the light receiver. These light receiving passages may be configured to only see light emitted by the laser beam. The
5 light receiving passage may be in the form of a cylindrical bore provided within a solid block providing the receiver body, the bore extending most of the way or completely through the block. A plurality of said light receiving passages may be aligned in a parallel relation through the solid block. The light
10 receivers may be provided at the end of each passage, the opposing end of the passages being exposed to and aligned with the lateral extent of the planar laser beam.

Alternatively, the light receiving means may include a focussing arrangement, for example a "cylindrical" lens in front of the light receivers. Each light receiver may be located at the end of a light receiving passage.
15 The passage may be provided by a box shaped enclosure separated into separate parallel passages by dividing walls. The cylindrical lens may be an elongate lens having a relatively uniform cross-section along its length. One side of the lens may have a constant radius of curvature, while the other side of the lens may be generally flat. Such a lens focuses in one plane only and
20 has a fixed focal point. It is however also envisaged that a plurality of lenses may be provided in front of the light receivers. The above described arrangement helps to ensure that the laser beam is focussed on to the light receivers, even where there is some displacement of the laser beams.

It has been found in practice that it is also possible to eliminate the
25 need for any separators in the enclosure for separating the planar laser beam. The enclosure may therefore be completely hollow except for the light receiver array at one end of the enclosure, and the cylindrical lens on the other side thereof. This is because as long as the planar laser beam enters the enclosure parallel to the sides of the enclosure, then all of the light receivers
30 will be receiving light. If the planar laser beam however enters at an angle to the sides of the enclosure, then a "shadow will be cast on at least one of the end light receivers of the light array thereby stopping the operation of the press.

WO 00/67932

PCT/AU00/00420

6

All the light receivers may be aligned with and exposed to the same continuous planar laser beam during operation of the safety system according to the present invention. Therefore any vibration of the press which results in lateral deflection of the laser beam within a predetermined range should not effect the operation of the receiving means. This is because all the light receivers may still be exposed to the same laser beam even when there is a lateral deflection of the laser beam as the width of the laser beam may be wider than the width of the light receiver array. The safety system according to the present invention can therefore be relatively insensitive to vibration of the press where the vibrations primarily result in lateral deflection of the laser beam.

As it can therefore be possible to avoid the need for any software compensation for the vibration effect on the laser beam, and any intersection by an object of the laser beam can result in a direct signal being provided to the control means to stop or prevent movement of the press thereby eliminating or minimising any delay from the breaking of the laser beam to the stopping of the press. The control means can be in the form of an electronic control unit which receives signals from the light receivers and controls the operation of the press.

To improve the operational control of the safety system, the light receivers may be grouped into separate sections. Each section of light receivers may provide their own separate control signal. The light receivers can, for example, be grouped into a front section, a mid section and a rear section.

Both the laser emitting means and the light receiving means may be respectively mounted on supports on opposing sides of the moveable section of the press. The supports may be respectively adjustable to allow the alignment and position of the laser emitting means to be adjusted. For example, where the moveable section is a bending or cutting blade, blades of different heights can be used, and the position of the laser emitting means and light receiving means will need to be adjusted. Alternatively, only the laser emitting means need be adjusted, the light receiving means remaining

WO 00/67932

PCT/AU00/00420

7

fixed. This is, for example, possible where the light receiving means includes a said focussing arrangement in front of the light receivers.

It will be convenient to further describe the invention by reference to the accompanying drawings which illustrate a preferred embodiment of the present invention. Other embodiments of the invention are possible, and consequently the particularity of the accompanying drawings is not to be understood as superseding the generality of the proceeding description of the invention.

In the drawings:

Figure 1 is a schematic view of a laser diode and lenses assembly according to the present invention;

Figure 2 is a cross-sectional view of a continuous planar laser beam emitted by the safety system taken along line A-A in Figure 1 prior to correction according to the present invention;

Figure 3 is a plan view of the continuous planar laser beam emitted by the safety system prior to correction according to the present invention;

Figure 4 is a plan view of a first preferred embodiment of the light receiving means according to the present invention;

Figure 5 is an end view of the light receiver assembly of Figure 4;

Figure 6 is a side view of a second preferred embodiment of the light receiving means according to the present invention;

Figure 7 is a perspective view of the cylindrical lens of Figure 7.

Figure 8 is a cross-sectional detail view of an industrial press showing the location of the laser beam; and

Figure 9 is a schematic view of the safety system mounted on an industrial press.

Referring initially to Figure 1, the industrial press safety system according to the present invention includes a laser emitting means 1 having a laser emitter 2, for example a laser diode, and a lenses assembly 8 for converting the laser beam 3 emitted from the laser emitter 2 into a continuous planar laser beam 9.

Figure 2 is a cross section of the continuous laser beam 9 emitted by the laser emitting means 1 taken along line A-A of Figure 1 prior to correction.

This laser beam 9 has a generally constant lateral width W along its' elongate extent. Furthermore, the continuous planar laser beam 9 has a generally constant thickness T . According to one possible configuration of the present invention, the laser beam 9 can have a lateral width of about 50 mm on average and a thickness of 3 mm on average. The angle of dispersion of the laser beam 9 is preferably equal to or less than 0.1%. It should be appreciated that alternative configurations are possible in dependence on the application of the safety system.

Returning to Figure 1, the lens assembly 8 includes a cylindrical prism 5 for initially expanding the laser beam 3 into a planar fan shaped beam 6. This planar fan shaped beam 6 then passes through a converging lens 7 for refocusing the fan shaped beam 6 into the planar laser beam 9 having a generally constant lateral width. It has been found that the light intensity when measured across the lateral width of the planar laser beam 9 will vary across that lateral width. This variation of light intensity is not normally visible to the eye, Figure 2 nevertheless schematically shows the light intensity variation, with areas 10 of increased light intensity distributed across the lateral extend of the last beam 9. It is considered that this is due to the refractive effect of the lenses 5, 7 which causes the parallel "lines of light" of the initial laser beam 3 to be deflected such that they are no longer parallel in the planar laser beam 9 emitted from the converging lens 7. A correcting lens 11 is therefore placed in front of the converging lens 7 to straighten the lines of light of the laser beam 9 so that they are generally parallel. The correcting lens 11 can be in the form of a lenticular lens having a plurality of lens sections which respectively straighten the portion of the laser beam passing through that section. It is however also envisaged that a plurality of parallel lenses may be placed side by side in front of the converging lens 7, each lens correcting a respective portion of the laser beam 9. The correcting lens 11 could alternatively be replaced by a lens series 17 including a concave lens 18 and convex lens 19 located one after each other and shown in dotted outline in Figure 1. It is also envisaged that the lens series 17 could be used in conjunction with the lenticular lens 11. Furthermore, additional correcting lenses could be added depending on the accuracy of the focusing required.

WO 00/67932

PCT/AU00/00420

9

Figure 3 helps to illustrate better the effect of not correcting the lines of light schematically shown as lines 15 in Figure 3. Where the planar laser beam 9 is left uncorrected from the converging lens 7, this results in an "overlapping" of the lines of light 15. By comparison, in the initial laser beam 3 from the laser emitter 2, the lines of light would be parallel, a typical characteristic of laser beam 5. Therefore, when an object intersects the planar laser beam 9, the overlapping of the lines of light 15 obliterates any shadow cast by the object 20. Therefore, the receiving means 22 will not detect any significant change in the light intensity of the planar laser beam 9 received by the light receiving means 22. The deflection of the lines of light 15 is typically less than 0.1° . Nevertheless, because of the long transmission distances, the non-parallel nature of the uncorrected planar laser beam 9 will have a significant effect on the operation of the safety system.

Figure 4 shows in detail the construction of the light receiving means 22. This light receiving means 22 includes a plurality of electronic light receivers 26 aligned along a straight line. To eliminate the effect of light other than that received from the planar laser beam 9, each light receiver 26 is placed at the end of an elongate cylindrical passage 24 provided within a solid block 23. The light receiving means 22 further includes a base plate 27 for supporting the light receivers 26 and a front transparent cover 25 for covering the inlet opening of the cylindrical passages 24.

Figure 5 is an end view of the light receiving means 22 showing the aligned cylindrical passages 24 covered by the transparent cover 25. The planar laser beam 9 is simultaneously received by all of the light receivers 26, the area of the laser beam shining on the light receiving means 22 being shown in dotted lines 30. It can be seen that any lateral movement of the laser beam 9 due to vibration of the industrial press will not normally effect the operation of the safety system, with the laser beam 9 still being received by all of the light receivers 26 unless it is bent more than the distance X as shown in Figure 5. Most of the vibration within industrial presses such as a press brake result, in side to side motion. Therefore, the effect of vibrating on the laser beam 9 is minimised by aligning the plane of the laser beam 9 horizontally. It is therefore generally not necessary to provide any software correction for the

WO 00/67932

PCT/AU00/00420

10

signals produced by the light receivers 26 due to the effect of vibration on the laser beam 9.

An alternative preferred embodiment of the light receiving means 22 of present invention is shown in Figure 6. Features which correspond to the arrangement shown in Figures 4 and 5 are designated with the same reference numeral. The light receivers 26 are located in the rear of an enclosure 38 and a "cylindrical" lens 37 is located in front of the light receivers 26 and extending in front of all the light receivers 26. The cylindrical lens 37, which is shown in perspective in Figure 7 has a forward side 39 with a constant radius of curvature. The rear side 40 of the lens 37 is generally flat. The cross-section of the lens 37 is generally constant along its length. In practice, the lens 37 is located in front of all the light receivers 26 so that the curve of the forward side of the lens 37 is running in a vertical plane. Such a lens 37 is typically about 50 mm in height. A series of parallel and generally vertical dividing walls 36 are provided with the enclosure 38 to separate the enclosure 38 into a series of parallel light receiving passages 24, with a light receiver 26 being provided at the end of each passage 24. It is however also possible to use a hollow enclosure 38 without any partitions as previously discussed.

Having such a cylindrical lens 37 ensures that whenever the laser beam 9 hits the lens 37 in the vertical plane, the light is focussed back to the light receivers 26 in that one plane. In other words, the lens 37 focuses light in one plane only. Such lens 37 also have a fixed focal point. This arrangement also ensures that the laser beam 9 will only be directed to the light receivers 26 if the beam 9 is horizontal (ie perpendicular) to the lens 37. The lens may allow a tolerance from the horizontal plane of typically about 1° , although this tolerance may be adjusted. This means that the light receivers 26 will only accept the laser beam 9 if it is running parallel to the component of the press being controlled, for example a movable blade 30 as shown in Figure 8. The dividing walls 36 within the enclosure 38 act to ensure that the light is coming straight to the light receivers 26 within said tolerance in this horizontal plane.

It is, however, also envisaged that a plurality of separate lenses be provided in front of the high receivers 26, with each lens focussing a

WO 00/67932

PCT/AU00/00420

11

respective section of the light beams. In this arrangement, the lenses could be of the more conventional circular type.

Figure 6 shows in dotted lines other positions of the leading edge of the blade 30 where different blades 30 are used. The laser beam 9 must therefore be repositioned for each different blade 30 as shown in Figure 6. The use of such a cylindrical lens 37 therefore allows the laser beam 9 to be at different heights due to differences in the depth of the blade 30 while still allowing the laser beam 9 to be focussed to the light receivers 26.

The light receivers 26 are positioned close together to thereby allow the laser beam 9 to be received across the width of the field of that laser beam 9. These light receivers 26 can be grouped to receive different segments of the beam 9, eg front section, mid section and rear section. This is so that, if required, an intersection of the laser beam 9 in different sections of the laser beam 9 can be responded to in different ways. For example, the intersection of the front section can result in the stopping and "jump back" of the movable blade 30. Intersection of the mid section of the laser beam 9 is used to trigger a "mute point" setting as well as provide a stop and jump back response of the blade 30. The mute point is the point beyond which the blade 30 will travel even if there is an intersection of the laser beam 9. Normally the laser beam 9 is triggered a short distance (typically approximately 4 mm) before it reaches the surface of the material to be bent and muted (ie. desensitized) to allow the bending process. It is considered that, at this distance, the smallest obstruction (ie a finger) could not be present. Finally, intersection of the rear section of the laser beam 9 will stop the blade 30, but without any jump back thereof. Also when switched into a special mode of operation, this rear section can be muted a few millimetres further away from the material being bent. Therefore, if a back gauge 50, a standard apparatus on many press brakes, is brought in close to the blade 30 to do very short bends so that it is close enough to intrude onto the rear section of the laser beam 9, the back gauge 50 will not interrupt the bending process (see Figure 8). This muting of the rear section of the laser beam 9 early, is considered safe because:

1. The rear of the press is far less likely to be accessed by the operators (and assistants) in normal working conditions; and

2. To help compensate (in this special mode only) the blade 30 stops at the mute point and needs a further foot switch application for the closing operation. This also ensures the operator knows he is in this special mode.

The safety system according to the present invention may also provide
5 other responses, for example, when the press is required to manufacture a box or tray where the sides thereof may be upstanding and may therefore intersect the laser beam 9 as the blade comes down. Therefore, at a "tray mode" of operation, when laser beam front section only is interrupted the first time, the blade 30 stops. If at least one of the other sections of the laser
10 beam 9 are clear, then the safety system allows a closing movement of the blade 30 after foot switch operated under this tray mode. This is to allow the sides of a tray or box to interrupt the front section of the laser beam 9 while still allowing the blade 30 to continue to move. The rear section of the laser beam 9 may also need to be "muted" to allow the end wall of the tray to be
15 formed. Therefore, the blade 30 will initially stop when the rear section is intercepted, but will continue following the pressing of the foot switch if the centre section is still clear. This mode always gives full protection of the full width of the laser beam 9 down to the upstand on the tray or box and, after a stop, only allows downward movement if the portion of the laser beam 9
20 directly under the blade 30 is still clear ensuring that fingers are not left under the blade in the final closing movement.

Figure 8 is a schematic cross sectional view showing the position of the planar laser beam 9 relative to the blade 30 and anvil 35 of a press brake. The planar laser beam 9 is located closely adjacent to the leading edge 32 of
25 the blade 30, the plane of the laser beam 9 being generally horizontal. The laser emitting means 1 and light receiving means 22 can be mounted on the blade 30 (see Figure 9) or on the support structure (not shown) for the blade 30. Therefore, where the press brake is of the type having a moveable blade 30, the safety system will move together with the blade 30. Also shown is the
30 movable back gauge 50 previously referred to.

Figure 9 shows the laser emitting means 1 and light receiving means 22 supported on brackets 45, 46, on the blade 30 of a press brake. This is applicable for both upstroking and downstroking press brakes.

The laser beam 9 is typically set at a distance in the press of 8 mm between the leading edge of the blade 30 and the centre line of the light beam 9. There is some tolerance allowed but essentially this distance must be equal to or greater than the stopping distance of the blade 30 after it has a stop signal.

The emitting means 1 and light receiving means 22 can be mounted on adjustable brackets 45, 46, so they can be accurately adjusted to this distance whenever the blade 30 is changed for different bending processes. (The vertical depth of these blades 30 can often vary.) The adjusting brackets 45, 46, are refined to make these adjustments relatively easy but due to the accuracy needed with laser beams 9, it does need some work by the operator to get both ends aligned properly.

The press will never operate until both ends are aligned and the light receiving means 22 is receiving from the laser emitting means 1.

The use of the cylindrical lens 37 is the light receiving means 22 allows it to be set at a height that can accommodate the shortest blade 30 and it will accept any blade, for example up to 50 mm deeper.

This means that the light receiving means 22 can stay fixed (only adjusted if the blade has an excessive depth) and the laser emitting means 1 is adjusted vertically to suit the blade 30. Because of this overall design, the adjusting for varying blades and alignment of both ends is very easy in this vertical plane. This also helps with any vibration (ramifications of this previously described) in the vertical plane as well.

WO 00/67932

PCT/AU00/00420

14

CLAIMS:

1. A safety system for an industrial press having a moveable section, the safety means including:
a laser emitting means for emitting a continuous planar laser beam having a generally constant lateral width;
a light receiving means for receiving the laser beam and for detecting when an object intersects the laser beam; and
a control means for stopping or preventing movement of the moveable section of the press when the receiving means detects that the laser beam has intersected an object.
2. A safety system according to claim 1, wherein the industrial press has a blade and an anvil moveable relative to each other, the safety system being locatable such that the planar laser beam is emitted immediately adjacent the leading edge of the blade.
3. A safety system according to claim 2, wherein the plane of the planar laser beam is at least substantially horizontal and is locatable between the blade and anvil of the press brake.
4. A safety system according to claim 2, wherein the plane of the planar laser beam is at least substantially vertical and is locatable in front of the blade.
5. A safety system according to any one of claims 2 to 4, wherein the laser emitting means and the light receiving means is mountable on or immediately adjacent the blade, and is movable with the blade when it is the moveable section of the press.
6. A safety system according to any one of the preceding claims, including a plurality of laser emitting means and associated said light receiving means for emitting a plurality of said planar laser beams.

WO 00/67932

PCT/AU00/00420

15

7. A safety system according to any one of the preceding claims, wherein the laser emitting means includes a laser emitter for emitting a laser beam, and a lens assembly for varying the configuration of the laser beam into a said planar laser beam of generally planar shape and having a generally constant lateral width.

8. A safety system according to claim 7, wherein the lens assembly includes a cylindrical prism for initially expanding the laser beam into laser beam having a planar fan shaped configuration, and a converging lens for refocussing the fan shaped laser beam to a planar laser beam having a generally constant lateral width.

9. A safety system according to claim 8, wherein the lens assembly further includes at least one correcting lens provided after the converging lens for straightening the lines of light of the planar laser beam.

10. A safety system according to claim 9, wherein the correcting lens includes a lenticular lens formed from one or more lens sections.

11. A safety system according to claim 9 or 10, wherein the correcting means includes a lens series having at least one convex lens and at least one concave lens.

12. A safety system according to any one of the preceding claims, wherein the light receiving means includes a receiver body, and a plurality of light receivers aligned along a common axis as a light receiver array and located at one end of the receiver body, wherein each light receiver is located at one end of a respective light receiving passage provided through the receiver body.

13. A safety system according to any one of the preceding claims, wherein the light receiving means includes a receiver body, a plurality of light receivers aligned along a common axis as a light receiver array and located at one end

of the receiver body, and a lens provided at the opposing end of the receiver body for focusing the planar laser beam onto the light receivers.

14. A safety system according to claim 13 wherein the lens is a cylindrical lens, the lens focusing the planar laser beam onto the light receivers even when the laser beam is displaced laterally from a plane extending through the light receivers.

15. A safety system according to claim 13 or 14, wherein the receiver body is an enclosure separated into separate parallel passages by dividing walls.

16. A safety system according to any one of claims 12 to 15, wherein the width of the planar laser beam is wider than the length of the light receiver array.

17. A safety system according to any one of claims 12 to 16, further including an electronic control unit for receiving control signals from the light receivers and for controlling the operation of the press, wherein the press is stopped when the receipt of the light of the laser beam to at least one of the light receivers is blocked due to a breaking of the planar beam.

18. A safety system according to claim 17, wherein the light receivers are grouped into separate sections, with each section of light receivers providing a separate control signal to the electronic control unit.

19. A safety system according to any one of the preceding claims, wherein both the laser emitting means and the light receiving means are respectively mounted on supports on opposing sides of the moveable section of the press, wherein at least one of the supports is adjustable to allow the alignment and position of at least one of the laser emitting means or the light receiving means to be adjusted.

WO 00/67932

PCT/AU00/00420

17

20. A safety system according to claim 19, wherein only the laser emitting means is adjustable, the light receiving means remaining in a fixed position.


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: B21D 55/00, F16P 3/00, 3/14	A1	(11) International Publication Number: WO 00/67932 (43) International Publication Date: 16 November 2000 (16.11.00)
(21) International Application Number: PCT/AU00/00420 (22) International Filing Date: 5 May 2000 (05.05.00) (30) Priority Data: PQ 0221 5 May 1999 (05.05.99) AU <i>05 Nov 01/30 mo</i> (71) Applicant (for all designated States except US): LAZER SAFE PTY LTD [AU/AU]; Unit 1, 131 Rokeby Road, Subiaco, W.A. 6008 (AU). (72) Inventor; and (75) Inventor/Applicant (for US only): APPELYARD, Robert, Meredith [AU/AU]; 12 Carron Rise, Hillarys, W.A. 6025 (AU). (74) Agent: WATERMARK PATENT & TRADEMARK ATTORNEYS; 4th Fl, "Durack Centre", 263 Adelaide Terrace, Perth, W.A. 6000 (AU).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.

(54) Title: INDUSTRIAL PRESS SAFETY SYSTEM



(57) Abstract



A safety system for an industrial press having a moveable section (30), the safety means including: a laser emitting means (1) for emitting a continuous planar laser beam (9) having a generally constant lateral width; a light receiving means (22) for receiving the laser beam and for detecting when an object intersects the laser beam; and a control means for stopping or preventing movement of the moveable section of the press when the receiving means detects that the laser beam has intersected an object.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.


AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

1/5



2/5

Fig 3.



3/5

Fig 4.





Fig 5.



4/5

Fig 6.





Fig 7



5/5

Fig 8.





Fig 9.



DOCKET NO. WATE-0011

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

Robert Meredith APPLEYARD

Group Art Unit: not yet known**Intl. Appln. No.:** PCT/AU00/00420**Examiner:** not yet assigned**Intl. Filing Date:** 05 May 2000**For:** INDUSTRIAL PRESS SAFETY SYSTEM**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a



Utility Patent



Design Patent

is sought on the invention, whose title appears above, the specification of which:



is attached hereto.

was filed on 05 May 2000 asInternational Application No. PCT/AU00/00420.

said application having been amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to be material to the patentability of this application in accordance with 37 CFR § 1.56.

DOCKET NO. WATE-0011

- 2 -

PATENT

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a-d) of any **foreign application(s)** for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of any application on which priority is claimed:

Priority Claimed (If X'd)	Country	Serial Number	Date Filed
<input checked="" type="checkbox"/>	Australia	PQ 0221	05 May 1999
<input type="checkbox"/>			
<input type="checkbox"/>			
<input type="checkbox"/>			

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to be material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Serial Number	Date Filed	Patented/Pending/Abandoned

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

Serial Number

Date Filed

DOCKET NO. WATE-0011

- 3 -

PATENT

I hereby appoint the following persons of the firm of **WOODCOCK WASHBURN LLP**,
One Liberty Place - 46th Floor, Philadelphia, Pennsylvania 19103 as attorney(s) and/or
agent(s) to prosecute this application and to transact all business in the Patent and Trademark
Office connected therewith:

David A. CherryReg. No. 35,099_____
Reg. No. _____

Address all telephone calls and correspondence to:

David A. Cherry
WOODCOCK WASHBURN LLP
One Liberty Place - 46th Floor
Philadelphia PA 19103
Telephone No.: **(215) 568-3100**
Facsimile No.: **(215) 568-3439**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Rec'd PCT/PTO 04 FEB 2002

09980562.061102

09/98 0562

DOCKET NO. : WATE-0011

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

Robert Meredith APPLEYARD

Serial No.: 09/980,562

Group Art Unit: not yet known

Intl. Application No.: PCT/AU00/00420

Examiner: not yet assigned

International Filing Date: 05 May 2000

For: INDUSTRIAL PRESS SAFETY SYSTEM

Assistant Commissioner for Patents
Washington, DC 20231

Sir:

ASSOCIATE POWER OF ATTORNEY

The undersigned, of the firm WOODCOCK WASHBURN LLP, One Liberty Place - 46th Floor, Philadelphia, Pennsylvania 19103, Attorney and/or Agents for Applicant(s), hereby appoints the following:

Richard E. Kurtz	Registration No. <u>19,263</u>	Janet E. Reed	Registration No. <u>36,252</u>
Dale M. Heist	Registration No. <u>28,425</u>	Jeffrey J. King	Registration No. <u>38,515</u>
John W. Caldwell	Registration No. <u>28,937</u>	Robert B. Washburn	Registration No. <u>16,574</u>
Gary H. Levin	Registration No. <u>28,734</u>	Norman L. Norris	Registration No. <u>24,196</u>
Steven J. Rocci	Registration No. <u>30,489</u>	Albert W. Preston, Jr.	Registration No. <u>25,366</u>
Dianne B. Elderkin	Registration No. <u>28,598</u>	Anthony J. Rossi	Registration No. <u>24,053</u>
John P. Donohue, Jr.	Registration No. <u>29,916</u>	Terence P. Strobaugh	Registration No. <u>25,460</u>
Henrik D. Parker	Registration No. <u>31,863</u>	Michael J. Swope	Registration No. <u>38,041</u>
Suzanne E. Miller	Registration No. <u>32,279</u>	Michael J. Bonella	Registration No. <u>41,628</u>
Lynn B. Morreale	Registration No. <u>32,842</u>	Harold H. Fullmer	Registration No. <u>42,560</u>
Mark DeLuca	Registration No. <u>33,229</u>	John E. McGlynn	Registration No. <u>42,863</u>
Joseph Lucci	Registration No. <u>33,307</u>	Jonathan M. Waldman	Registration No. <u>40,861</u>
Michael P. Dunnam	Registration No. <u>32,611</u>	Chad Ziegler	Registration No. <u>44,273</u>
Michael D. Stein	Registration No. <u>34,734</u>	Gwilym J.O. Attwell	Registration No. <u>45,449</u>
Albert J. Marcellino	Registration No. <u>34,664</u>	David N. Farsiou	Registration No. <u>44,104</u>
David R. Bailey	Registration No. <u>35,057</u>	Paul K. Legaard	Registration No. <u>38,534</u>
Doreen Yatko Trujillo	Registration No. <u>35,719</u>	Steven H. Meyer	Registration No. <u>37,189</u>
Barbara L. Mullin	Registration No. <u>38,250</u>	Paul B. Milcetic	Registration No. <u>46,261</u>
Michael P. Straher	Registration No. <u>38,325</u>	Joseph R. Condo	Registration No. <u>42,431</u>
Kevin M. Flannery	Registration No. <u>35,871</u>	Michael K. Jones	Registration No. <u>41,100</u>
Lynn A. Malinoski	Registration No. <u>38,788</u>	Frank T. Carroll	Registration No. <u>42,392</u>
Steven B. Samuels	Registration No. <u>37,711</u>	Thomas E. Watson	Registration No. <u>43,243</u>

DOCKET NO. : WATE-0011

- 2 -


PATENT

Eric H. Vance	Registration No. <u>47,151</u>	Sharon Fenick	Registration No. <u>45,269</u>
Peter M. Ullman	Registration No. <u>43,963</u>	Daniel D. Biesterveld	Registration No. <u>45,898</u>
Richard B. LeBlanc	Registration No. <u>39,495</u>	Phillip A. Singer	Registration No. <u>40,176</u>
Joseph D. Rossi	Registration No. <u>47,038</u>	Richard D. Watkins	Registration No. <u>P50,993</u>
Rosaleen P. Morris-Oskanian	Registration No. <u>47,321</u>	Wendy A. Choi	Registration No. <u>36,697</u>
George J. Awad	Registration No. <u>46,528</u>	Rebecca M. Hale	Registration No. <u>45,680</u>
Steven D. Maslowski	Registration No. <u>46,905</u>	Christine A. Goddard	Registration No. <u>46,731</u>
S. Maurice Valla	Registration No. <u>43,966</u>	Ellen M. Klann	Registration No. <u>44,836</u>
Emma R. Dailey	Registration No. <u>48,491</u>	Andrew J. Hagerty	Registration No. <u>44,141</u>
Vincent J. Roccia	Registration No. <u>43,887</u>	Scott E. Scioli	Registration No. <u>47,930</u>
Robin S. Quartin	Registration No. <u>45,028</u>		
Patrick J. Farley	Registration No. <u>42,524</u>		
Gregory L. Hillyer	Registration No. <u>44,154</u>		
Stephen C. Timmins	Registration No. <u>48,481</u>		
Erich M. Falke	Registration No. <u>49,049</u>		
Jane E. Ingles	Registration No. <u>48,444</u>		
Susan C. Murphy	Registration No. <u>46,221</u>		
Raymond N. Scott, Jr.	Registration No. <u>48,666</u>		
David L. Marcus	Registration No. <u>46,897</u>		
Lawrence A. Aaronson	Registration No. <u>38,369</u>		
John A. Harrelson	Registration No. <u>42,637</u>		

76

his/her associates with full power to prosecute the above-identified application and to transact all business in the Patent Office connected therewith and requests that correspondence continue to be directed to the firm of WOODCOCK WASHBURN LLP at the above address.

Date: 2/4/02



 David A. Cherry
 Registration No. 35,099

Woodcock Washburn LLP
 One Liberty Place - 46th Floor
 Philadelphia PA 19103
 Telephone: (215) 568-3100
 Facsimile: (215) 568-3439

DOCKET NO. WATE-0011

- 4 -

PATENT

Name: <u>Robert Meredith APPLEYARD</u>	 Signature	
Mailing Address: 12 Carron Rise, Hillarys W.A. 6025 AUSTRALIA		Date of Signature: <u>7-1-02.</u>
City/State of Actual Residence: <u>Hillarys, W.A., AUSTRALIA</u> <i>AKX</i>		